Retrofit Axles
Assembly Instructions

7030 E 46th Avenue Dr, Denver, CO 80216, United States
support@hensleyseeds.com | hensleyseeds.com

These instructions apply to the following parts:

6198: Retrofit Axle – 24”
6196: Retrofit Axle – 32”
6195: Retrofit Axle – 36”

For use with:

7775: Infinite Dibbler Frame – 24”
7776: Infinite Dibbler Frame – 32”
7777: Infinite Dibbler Frame – 36”
7778: Two-Person Infinite Dibbler Frame – 36”

Also required:

6199: Rolling Dibbler Wheel(s)

Assembly Instructions:

1. Remove the existing axle from the frame by sliding the rubber rings off the axle support pins and removing the pins from the frame. Set the old axle aside but keep the rest of the parts handy.





Copyright © 2026 Hensley’s Seed Co. All rights reserved.

2. Attach Rolling Dibbler Wheels (item , sold separately) in the desired location(s) along the Retrofit Axle, using the clevis pin included with each wheel. Holes are spaced at 1” intervals.



3. Install the retrofit axle onto the frame using the same axle support pins. Move the rubber rings back onto the flat part of the pin.





Copyright © 2026 Hensley’s Seed Co. All rights reserved.

4. Once the axle is installed, the Rolling Dibbler Wheels can be moved along the axle. To add or remove wheels, repeat the axle installation process.



Important Notes:

- This Retrofit Axle allows use of Rolling Dibbler Wheels with your existing Two Bad Cats Infinite Dibbler. However, you cannot mix Two Bad Cats wheels (no longer available) with Rolling Dibbler Wheels. Keep the original axle if you would like to swap between the wheel systems.

- Rolling Dibbler Wheels work with the following products:
  - Single-Row Rolling Dibbler
  - Infinite Dibbler Frame – 24” (with axle)
  - Infinite Dibbler Frame – 32” (with axle)
  - Infinite Dibbler Frame – 36” (with axle)
  - Two-Person Infinite Dibbler Frame – 36” (with axle)

Copyright © 2026 Hensley’s Seed Co. All rights reserved.